



**EJES A TORSIÓN DE CAUCHO  
SIN FRENO  
Revisión X - Abril 2019**

Artículo	Carga máx. [kg]	Bulón	Disposición	Cotas generales				Posición de chasis y guardabarros						
				A [mm]	B [mm]	C [mm]	α nom. [°]	h [mm]			α [°]			y [mm]
								(1)	(2)	(3)	(1)	(2)	(3)	
ETG500	500	M12x1,5	4x98/100/108	1000 min 1900 max	235	1470 min 2370 max	25	104±5	74±5	64±4	20±3	8±3	4±2	90
ETG750	750	1/2"x20h	5x114,3	1000 min 1900 max	235	1470 min 2370 max	25	113±2	76±6	65±4	25±1	11±2	7±3	100
ETG1000	1000	M12x1,5	4x98/100/108	1000 min 1900 max	235	1470 min 2370 max	25	113±4	79±4	71±4	23±2	10±2	6±2	90
ETG1300	1300	1/2"x20h	5x114,3/139,7 6x139,7	1000 min 1900 max	235	1470 min 2370 max	25	118±3	78±3	68±3	25±1	9±1	5±1	110
ETG1500	1500	1/2"x20h	5x114,3/139,7 6x139,7	1000 min 1900 max	235	1470 min 2370 max	25	118±4	81±6	69±6	24±2	10±2	6±2	100
ETG1800	1800	1/2"x20h	5x139,7 6x139,7	1000 min 1900 max	260	1520 min 2420 max	25							
ETG2000	2000	1/2"x20h	5x139,7 6x139,7	1000 min 1900 max	260	1520 min 2420 max	25	138±4	104±10	90±10	25±2	12±4	7±4	100
ETG2500	2500	1/2"x20h	5x139,7 6x139,7	1000 min 1900 max	260	1520 min 2420 max	25	137±2	108±3	92±3	25±1	13±1	7±1	110
ETG3000	3000	3/4"x11/8"REF 3/4"x16h	5x203,2	1000 min 1900 max	260	1520 min 2420 max	30	152±1	118±3	105±2	32±1	18±2	13±1	100
		5/8"x16h	6x184,15											
		5/8"x16h	8x165,1/170/184,15											
		M18x1,5	6x205											
ETG3500	3500	3/4"x11/8"REF 3/4"x16h	5x203,2	1000 min 1900 max	260	1520 min 2420 max	30	152±1	113±3	100±2	32±1	16±2	10±1	105
		5/8"x16h	6x184,15											
		5/8"x16h	8x165,1/170/184,15											
		M18x1,5	6x205											

**Referencias:**

(1): sin carga; (2): carga máxima; (3): sobrecarga (50% de carga máxima)

